



PCB LAYOUT

SPECIFICATIONS

Housing: Thermoplastic, UL94V-0
 Color: Black
 Contact: Copper Alloy
 Shell: Zinc Alloy
 Voltage Current Rating: 0.5AMP. 250V AC
 Insulation Resistance: 500M Min.
 Contact Resistance: 80m Max.
 Dielectric Withstanding Voltage: 500V AC
 Temperature Range: -25 ° C to +70 ° C

No. of Pins	DME NSONS						
	A	B	C	D	E	F	G
14	7.62	9.52	12.6	29.51	23.61	17.25	19.58
20	11.43	13.1	16.43	33.32	27.46	21.06	23.39
26	15.24	17.1	20.24	37.13	31.26	24.76	27.2
36	21.59	23.4	26.5	43.48	37.61	31.11	33.55
50	30.48	32.29	35.39	52.37	46.5	40.0	42.44

MCR-nP SCS 母座 90°

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG	0.0
F5	±0.3
F10	±0.5
F15	±0.5
UNIT:	MM

SCALE: 1:1
 DRAWN: LI BEI LIN
 DATE: 30/08/09
 CHECKED: _____
 APPROVED: _____

PRODUCT NO.: _____
 FILE NAME: _____

1 2 3 4 5 6 7 8 9